





# Specifications to help you choose



Find the best HP Multi Jet Fusion 3D Printing Solution that addresses your needs, all the way from adoption to scale.

|  | Adopt  | Grow   |   | Scale   |
|--|--|--|---|---|
|  | HP Jet Fusion 5000 3D Printer  | HP Jet Fusion 5200 Series 3D Printing Solution   | HP Jet Fusion 5400 Series 3D Printing Solution  | HP Jet Fusion 5600 Series 3D Printing Solution  |
|  |   |    |                |    |
| Capacity   | Industrial prototyping and final part production environments producing up to 2 build per week (up to 200 parts per week)  | Final parts production environments producing over 200 parts per week <sup>1</sup>   | Final parts production environments producing over 550 parts per week <sup>2</sup>                | Final parts production environments producing over 550 parts per week <sup>3</sup>  |
| Upgrade path   | HP Jet Fusion 5200 3D Series Printing Solution   | HP Jet Fusion 5400 3D Series Printing Solution<br>HP Jet Fusion 5600 3D Series Printing Solution   | HP Jet Fusion 5420W 3D Printing Solution<br>HP Jet Fusion 5420W Pro 3D Printing Solution          | HP Jet Fusion 5620 3D Printing Solution<br>HP Jet Fusion 5620 Pro 3D Printing Solution  |
| Running costs  | Good   | Better   | Better  | Best  |
| Capability to print in   | Grey   |  | White   | Grey and Light Grey <sup>5</sup>  |
| Current material breadth   | HP 3D HR PA 11 / HP 3D HR PA 12, enabled by Evonik / HP 3D HR PA 12 S, enabled by Arkema / HP 3D HR PP enabled by BASF / HP 3D HR PA 12 GB / BASF Ultrasint® TPU*01 / ESTANE® 3D TPU* M88A | HP 3D HR PA 11 / HP 3D HR PA 12 S, enabled by Arkema / HP 3D HR PA 12, enabled by Evonik / HP 3D HR PA 12 GB / HP 3D HR PP enabled by BASF / BASF Ultrasint® TPU01 / ESTANE® 3D TPU M88A | HP 3D HR PA 12 W  | HP 3D HR PA 11 <sup>15</sup><br>HP 3D HR PA 12, enabled by Evonik<br>HP 3D HR PA 12 S, enabled by Arkema<br>HP 3D HR PA 12 W<br>BASF Ultrasint® TPU01 |
| Effective building volume (X, Y, Z)  | 380 x 284 x 250mm<br>(15 x 11.2 x 9.9in)   |  | 380 x 284 x 380 mm<br>(15 x 11.2 x 15 in)   |   |
| Print time <sup>6</sup>  | 8hrs (Balanced print mode)<br>8.27 hrs - including job cool done<br>(Balanced print mode)  | 12 hrs (Balanced print mode)<br>9.40 hrs (Fast print mode)<br>13.50 hrs (Robust print mode)  | 13.50 (Balanced print mode)   | 11.8h (Balanced print mode)   |
| Recommended HP 3D Solution Services <sup>7,8,9</sup>                                 | 3DaaS only   | HP 3D Production Care<br>(next business day on-site response time)   | HP 3D Shared Care<br>(HP 3D Proactive Remote Service and next business day on-site response time) |   |
| Software   | HP 3D Center <sup>10</sup> / HP 3D Build Manager / HP 3D Command Center  | HP 3D API <sup>11</sup> / HP 3D Center <sup>10</sup> / HP 3D Build Manager / HP 3D Command Center  |   |   |
| HP 3D Process Development Package compatibility <sup>12</sup>                        | ✗  | ✗  | ✗   | ✓   |
| HP Jet Fusion 3D Automation Accessory compatibility <sup>13</sup>                    | ✗  | ✓  | ✓   | ✓   |
| Material handling workflow <sup>12</sup>   | Manual Powder Handling, HP Jet Fusion 5200 3D Processing Station upgrade possible  | HP Jet Fusion 5200 3D Processing Station, HP Jet Fusion 3D Powder Handling Automation Solution   | HP Jet Fusion 5400 3D Processing Station  | HP Jet Fusion 5200 3D Processing Station, HP Jet Fusion 3D Powder Handling Automation Solution  |
| HP Jet Fusion 5200 Series 3D Automatic Unpacking Station compatibility <sup>12</sup> | ✗  | ✓  | ✓   | ✓   |
| Doorway clearance <sup>14</sup>  | 2320 mm (91.3 in)  |  |   |   |
| Operating footprint <sup>14</sup>  | 21.5 m <sup>2</sup> (232 ft <sup>2</sup> )   |  | 22.7 m <sup>2</sup> (245 ft <sup>2</sup> )  | 21.5 m <sup>2</sup> (232 ft <sup>2</sup> )  |

Learn more at [hp.com/go/3DPrint](https://hp.com/go/3DPrint)

1. The HP Jet Fusion 5200 Series achieves a favorable cost per part versus the HP Jet Fusion 4200 for production volumes of over 200 parts per week. Part is 30 cm<sup>3</sup> part at a 10% packing density using HP 3D High Reusability PA 12 material, and up to 80% powder reusability ratio. Assuming 5 years of depreciation, 292 working days per year and assuming one printer, one processing station, and two build units for both HP Jet Fusion 4200 and HP Jet Fusion 5200 3D Printing Solutions.
2. The HP Jet Fusion 5400 Series Printing Solution achieves a favourable cost per part versus the HP Jet Fusion 4200 for production volumes of over 200 parts per week. Part is 30 cm<sup>3</sup> part at 8% packing density using HP 3D High Reusability PA 12 W material, and up to 75% powder reusability ratio. Assuming 5 years of depreciation, 292 working days per year and assuming one printer, one processing station, and two build units for both HP Jet Fusion 4200 and HP Jet Fusion 5400 Series 3D Printing Solutions.
3. The HP Jet Fusion 5600 Series achieves a favorable cost per part versus the HP Jet Fusion 5200 for production volumes of over 200 parts per week. Part is 30 cm<sup>3</sup> part at a 10% packing density using HP 3D High Reusability PA 12 material, and recommended powder reusability ratios. Assuming 5 years of depreciation, 292 working days per year and assuming one printer, one processing station, and two build units for both HP Jet Fusion 5200 and HP Jet Fusion 5600 3D Printing Solutions.
4. HP Jet Fusion 5200 3D Processing Station needed.
5. A light grey color can be achieved using the HP 3D HR PA12 W on the HP Jet Fusion 5600 Series 3D Printing Solution.
6. Printing time for the HP Jet Fusion 5200 Series 3D Printing Solution and the HP Jet Fusion 5600 Series 3D Printing Solution is based on printing with the HP 3D HR PA 12 material, enabled by Evonik.
7. Each service offered during local standard HP business hours on normal business days, excluding local HP holidays; availability may vary based on location. Coverage window includes remote and on-site diagnoses, which may affect on-site response time.
8. Available in most countries, subject to Terms & Conditions of HP Limited Warranty and/or Service Agreement. Please consult your local sales representative for further details.
9. Service level agreement can be customized. For more information contact your local sales representative.
10. Compatible software, service and/or solution.
11. HP 3D API Core available for the HP Metal Jet S100 Printing Solution and for HP Jet Fusion 3D Printing Solutions. HP 3D API Advanced only available for the HP Metal Jet S100 Printing Solution.
12. Compatible software, service and/or solution. Additional purchase required.
13. Compatible with HP 3D HR PA 12, enabled by Evonik, HP 3D HR PA 12 S, enabled by Arkema, HP 3D HR PA 12 W, HP 3D HR PA 12 GB, HP 3D HR PA 11, and HP 3D HR PP, enabled by BASF.
14. Measurement without the HP Jet Fusion 3D Automation Accessory.
15. Available in Spring 2025.

© Copyright 2022-2024 HP Development Company, L.P.

The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

4AA7-4999ENA, June 2024

